

## CAPICORDA DI POTENZA

RAME RICOTTO E STAGNATO (PURO AL 99,9%).

CONFORME ALLE NORME DIN40500 E IEC1238-1:1993

TIPO "A" con occhio di controllo

TIPO "B" senza occhio



Codice	Ø occhio mm	Sezione mm <sup>2</sup>	Conf.
CW01-005	5	1,5	100
CW01-006	6	1,5	100
CW02-004	4	2,5	100
CW02-005	5	2,5	100
CW02-006	6	2,5	100
CW03-005	5	4	100
CW03-006	6	4	100
CW03-008	8	4	100
CW04-004	4	6	100
CW04-005	5	6	100
CW04-006	6	6	100
CW04-008	8	6	100
CW04-010	10	6	100
CW04-012	12	6	100
CW05-005	5	10	100
CW05-006	6	10	100
CW05-008	8	10	100
CW05-010	10	10	100
CW05-012	12	10	100
CW06-005	5	16	100
CW06-006	6	16	100
CW06-008	8	16	100
CW06-010	10	16	100
CW06-012	12	16	100
CW07-005	5	25	100
CW07-006	6	25	100
CW07-008	8	25	100
CW07-010	10	25	100
CW07-012	12	25	100
CW07-014	14	25	100
CW08-006	6	35	100
CW08-008	8	35	100
CW08-010	10	35	100
CW08-012	12	35	100
CW08-014	14	35	100

Codice	Ø occhio mm	Sezione mm <sup>2</sup>	Conf.
CW09-006	6	50	100
CW09-008	8	50	100
CW09-010	10	50	100
CW09-012	12	50	100
CW09-014	14	50	100
CW09-016	16	50	100
CW10-006	6	70	50
CW10-008	8	70	50
CW10-010	10	70	50
CW10-012	12	70	50
CW10-014	14	70	50
CW10-016	16	70	50
CW11-008	8	95	50
CW11-010	10	95	50
CW11-012	12	95	50
CW11-014	14	95	50
CW11-016	16	95	50
CW12-010	10	120	30
CW12-012	12	120	30
CW12-014	14	120	30
CW12-016	16	120	30
CW13-010	10	150	10
CW13-012	12	150	10
CW13-014	14	150	10
CW13-016	16	150	10
CW13-020	20	150	10
CW14-010	10	185	4
CW14-012	12	185	4
CW14-014	14	185	4
CW14-016	16	185	4
CW14-020	20	185	4
CW15-016	16	300	6
CW15-020	20	300	6
CW16-016	16	400	1
CW16-020	20	400	1